The CDF Time of Flight Detector

Jónatan Piedra, Rocío Vilar Instituto de Física de Cantabria / CSIC-UC (on behalf of CDF TOF group*)

> *FNAL, LBL, MIT, U. Penn, INFN Pisa, INFN Roma, Kyungpook Ntl. U., Seoul Ntl. U., SungKyunKwan U., IFCA, U. Tsukuba

October 21, 2003 IEEE NSS/MIC PORTLAND, Oregon

Outline

- TOF detector in CDF
- TOF technique
- Calibrations
- t_o calculation
- TOF triggers
- TOF resolution
- Physics with TOF
 - B physics
 - Minimum bias QCD
 - Exotic physics
- Conclusions



TOF in CDF

Cylinder of 216 scintillator bars at radial distance from beam pipe 1.4 m


- Bicron BC-408
- Att. length 2.5 m
- Fast rise time 0.9 ns
- 4 x 4 x 280 cm

PMT at each end

- Hamamatsu R7761
- Fine mesh, 19 stage
- Gain reduction 500 @ B=1.4 T
- Small TTS: 250-400ps


TOF Milestones

- Test run (5% "full scale") in 1995
- Approved in January 1999
- Fully installed in August 2000
- Electronics in August 2001
- Stable data taking from October 2001



TOF technique

Objective: flight time of the particle from collision to TOF detector



$$TDC = C_S - (t_0 + tof + t_s + t_c + t_w)$$

Calibrations (I)

- ADC calibration
 - Pedestals measurement and linearity check
- Time-to-Amplitude Converter (TAC) calibration
 - Digital delay generator to study non-linear response

on-line

off-line

- Time walk effect
 - Due to dependence of discriminator time on pulse height (~2 ns)
- Speed of signal propagation in bars
 - Times depend on z position of hit along the bar (~20 ns)
- Channel-to-Channel time offset
 - Includes cable lengths and clock signals (~1 ns)
- Residual correction in z position along the bar
 - Residual dependence of time with the position (~200 ps)

Calibrations (II)

Time walk correction

Due to leading edge pick-off method

Larger pulses fire the discriminator at earlier time than smaller pulses

Effect studied with tracks passing through two adjacent bars of scintillator


$$F(Q) = \frac{-\alpha}{\sqrt{Q}}$$


Time difference vs. z

The effective speed of light comes from the fitted slope

Time walk dependence is absorbed in the fit

$$t_{E} - t_{W} = t_{E}^{0} - t_{W}^{0} - [F_{E}(Q) - F_{W}(Q)] + 2z/s$$





t₀ calculation


The CDF TOF detector has unique conditions Long bunches $\sigma_z \sim 30$ cm $\Rightarrow \Delta t_0 = \sigma_z/c \sim 1$ ns $>> \sigma_{tof}$

Need to calculate t₀ event by event to achieve the design resolution

Perform likelihood fit track by track ≥3 good tracks/event but the track of interest

For each track hitting TOF $t_0^{\pi,k,p} = \text{TDC} - t_c - t_w(Q) - t_s(z) - \text{TOF }^{\pi,k,p}$ Choose π,k,p with probabilities $f_{\pi,k,p}$ ($\Sigma f_i \equiv 1$)

$$\sigma(t_0) \sim \frac{100 \text{ ps}}{\sqrt{N_{\text{tracks}}}}$$



TOF triggers


Low amplitude threshold


Minimum Ionizing Particle (MIP)

COT multiplicity > 22 14 MIPs hits in TOF (MIP > 400 ADC)

QCD physics

Studies of Minimum Bias (high multiplicity) events Try to explain non perturbative soft interactions





High amplitude threshold

Highly Ionizing Particle (HIP)

Trigger rate is kept below ½ Hz

Data shows a linear response from zero to four MIPs

Exotic physics


Dirac Magnetic Monopole Search
Deposit large amount of energy along the way

TOF resolution (pure pion sample)


- Data (\sim 65 pb⁻¹): two displaced tracks, P_t > 2 GeV/c
- Decay of interest: $D^* \to D^0 \pi^{\pm} \to [K\pi] \pi^{\pm}$



$$\Delta t \equiv Tof_{measured} - Tof_{expected \pi}$$



Narrow gaussian \Rightarrow 129 \pm 2 ps Broad gaussian \Rightarrow 378 \pm 9 ps t_0 correlation between two pions Get t_0 from fast π ($|\Delta t|$ < 0.1 ns), used to the second π



Narrow gaussian \Rightarrow 118 \pm 2 ps Broad gaussian \Rightarrow 340 \pm 22 ps

TOF resolution (high P_t samples)


 t_0 is calculated for the two highest momentum tracks assuming speed of light

Sample, high P_t electrons Decay of interest

$$Z^0 \rightarrow e^+e^-$$

TOF resolution

$$(175\pm8)/\sqrt{2} = 124\pm6 \text{ ps}$$




Also done with other high P_t samples:


- Dijet with resolution of 123 \pm 11 ps
- Multijets with resolution of 139 ± 4 ps

Physics with TOF (I)

B physics TOF designed mainly for flavor tagging

Flavor oscillation and CP asymmetry → determine the B flavor via kaon ID






Opposite side tagging: exploits B weak decays $b \rightarrow c \rightarrow s$ $(b \rightarrow K-X)$ but $\overline{b} \rightarrow K+X)$


Same side tagging: exploits correlation between b flavor and particles produced in hadronization $\pi \leftrightarrow B^0$, $\pi^- \leftrightarrow \overline{B^0}$, $K^+ \leftrightarrow B^0_s$

Physics with TOF (II)

B physics $\Lambda_b \to \Lambda_c | \nu \to [pK\pi] | \nu$

TOF (and dEdx) used to identify the proton to reduce greatly backgrounds





Particle ID with pseudo likelihood ratio (signal efficiency = 64 %)


 Λ_b lifetime can be measured using an unbinned likelihood fit to the proper decay lengths of the $\mu+\Lambda_c$


Physics with TOF (III)

Exotic physics

Massive long-lived charged particles (CHAMPS)

High P_t muon events
Large energy loss
Isolated candidate tracks
Search for slow particles






Cosmic rays rejection High Pt muon pairs

High P_t physics Significant background to Electroweak & Exotic physics

Conclusions

- TOF fully operational and reliably working since October 2001
- Resolution sensitive to t₀ calculation, depends on the analysis
- Trigger hardware (MIP and HIP) installed and working
- Being used for several physics analysis
- Flavor Tagging results soon

Backup slides



TOF group at CDF

FNAL: C. Grozis, R. Kephart, R. Stanek

LBL: Y.K. Kim, G. Veramendi

MIT: K. Anikeev, G. Bauer, I.K. Furic, A. Korn, I. Kravchenko,

M. Mulhearn, Ch. Paus, S. Pavlon, K. Sumorok

U.Penn: C. Chen, M. Jones, W. Kononenko, J. Kroll, G.M. Mayers,

F.M. Newcomer, R.G.C. Oldeman, D. Usynin, R. Van Berg

INFN Pisa: G. Bellettini, C. Cerri, A. Menzione, F. Spinella, E. Vataga

INFN Roma: S. De Cecco, D. De Pedis, C. Dionisi, S. Giagu,

M. Rescigno, L. Zanello

Kyungpook Ntl. U.: D.H. Kim, M.S. Kim, Y. Oh

Seoul Ntl. U.: M. Ahn, B.J. Kim, S.B. Kim

SungKyunKwan U.: I. Cho, J. Lee, I. Yu

IFCA: J. Fernández, G. Gómez, J. Piedra, T. Rodrigo, A. Ruiz, I. Vila, R. Vilar

U. Tsukuba: H. Kaneko, A. Kazama, S. Kim, K. Sato, F. Ukegawa















Mechanics and phototubes

- Custom-made Hamamatsu R7766
 - ▶ 19 dynode (high gain)
 - Fine mesh (increased tolerance @ 1.4 T)
 - Small size 1.5 x 2.5 inches
 - Operated with a positive HV up to 2500 V
 - ► Gain reduction factor at B = 1.4 T ~ 500







- Scintillators assembled in 72 triplets
- PMT in Alu holders
- Tight radial clearance (few mm)

TOF signal path


Electronics contribution to overall resolution < 25 ps



Mass separation



Monopoles



CHAMPS

